



STATE OF IDAHO  
DEPARTMENT OF  
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, ID 83706 • (208) 373-0502  
www.deq.idaho.gov

Brad Little, Governor  
John Tippetts, Director

June 26, 2020

Dennis E. Achey, Site Manager  
Amvac Chemical Corporation  
6556 Simpkin Ln.  
Marsing, Idaho 83639

RE: Facility ID No. 073-00016, Amvac Chemical Corporation, Marsing  
Final Permit Letter

Dear Dennis E. Achey:

The Department of Environmental Quality (DEQ) is issuing Permit to Construct (PTC) No. P-2020.0012 Project 62409 to Amvac Chemical Corporation located at Marsing for the initial permit for an existing seed treatment chemical formulation and packing operation. This PTC is issued in accordance with IDAPA 58.01.01.200 through 228 (Rules for the Control of Air Pollution in Idaho) and is based on the certified information provided in your PTC application received March 10, 2020.

This permit is effective immediately. This permit does not release Amvac Chemical Corporation from compliance with all other applicable federal, state, or local laws, regulations, permits, or ordinances.

Pursuant to the Construction and Operation Notification General Provision of your permit, it is required that construction and operation notification be provided. Please provide this information as listed to DEQ's Boise Regional Office, 1445 N. Orchard, Boise, ID 83706, Fax (208) 373-0287.

In order to fully understand the compliance requirements of this permit, DEQ highly recommends that you schedule a permit handoff meeting with David Luft, Air Quality Manager, at (208) 373-0201 to review and discuss the terms and conditions of this permit. Should you choose to schedule this meeting, DEQ recommends that the following representatives attend the meeting: your facility's plant manager, responsible official, environmental contact, and any other staff responsible for day-to-day compliance with permit conditions.

Pursuant to IDAPA 58.01.23, you, as well as any other entity, may have the right to appeal this final agency action within 35 days of the date of this decision. However, prior to filing a petition for a contested case, I encourage you to contact Joe Palmer at (208) 373-0502 or [joe.palmer@deq.idaho.gov](mailto:joe.palmer@deq.idaho.gov) to address any questions or concerns you may have with the enclosed permit.

Sincerely,

A handwritten signature in cursive script that reads "Darin Pappas".

for, Mike Simon  
Stationary Source Bureau Chief  
Air Quality Division

MS\jp

Permit No. P-2020.0012 PROJ 62409

Enclosures

# Air Quality

## PERMIT TO CONSTRUCT

---

**Permittee** Amvac Chemical Corporation  
**Permit Number** P-2020.0012  
**Project ID** 62409  
**Facility ID** 073-00016  
**Facility Location** 6556 Simpkin Ln.  
Marsing, Idaho 83639

### Permit Authority

This permit (a) is issued according to the “Rules for the Control of Air Pollution in Idaho” (Rules), IDAPA 58.01.01.200–228; (b) pertains only to emissions of air contaminants regulated by the State of Idaho and to the sources specifically allowed to be constructed or modified by this permit; (c) has been granted on the basis of design information presented with the application; (d) does not affect the title of the premises upon which the equipment is to be located; (e) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (f) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; and (g) in no manner implies or suggests that the Idaho Department of Environmental Quality (DEQ) or its officers, agents, or employees assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment. Changes in design, equipment, or operations may be considered a modification subject to DEQ review in accordance with IDAPA 58.01.01.200–228.

**Date Issued** June 26, 2020

  
**Joe Palmer, Permit Writer**

---

  
**for, Mike Simon, Stationary Source Bureau Chief**

---

## Contents

|   |                                 |    |
|---|---------------------------------|----|
| 1 | Permit Scope .....              | 3  |
| 2 | Insecticides & Fungicides ..... | 4  |
| 3 | Herbicides .....                | 6  |
| 4 | Flour Processing .....          | 8  |
| 5 | General Provisions .....        | 10 |

# 1 Permit Scope

## Purpose

1.1 This is an initial permit to construct (PTC) for the existing Amvac Chemical Corporation (Amvac) facility. Previously, Amvac was exempt from air permitting requirements.

## Regulated Sources

Table 1.1 lists all sources of regulated emissions in this permit.

**Table 1.1 Regulated Sources**

| Permit Section | Source                                | Control Equipment  |
|----------------|---------------------------------------|--|
| 2              | <u>Insecticides &amp; Fungicides:</u> | <u>Insecticides &amp; Fungicides - (4) Mac Flo Filtration Units:</u><br>Manufacturer: Donaldson Torit<br>Model: USAF-C0080-2-L<br>Filter Type: ProTura Nanofiber<br>PM <sub>10</sub> control efficiency: 98.3% |
| 3              | <u>Herbicides:</u>                    | <u>Herbicide – (1) Mac Flo Filtration Unit:</u><br>Manufacturer: Donaldson Torit<br>Model: USAF-C0080-2-L<br>Filter Type: ProTura Nanofiber<br>PM <sub>10</sub> control efficiency: 98.3%                      |
| 4              | <u>Flour Processing:</u>              | <u>Flour Baghouse:</u><br>Manufacturer: US Air Filtration<br>Model: 16 oz Polyester<br>Type: Polyester Needle Punched Felt<br>PM <sub>10</sub> control efficiency: 99.8%                                       |

## 2 Insecticides & Fungicides

### 2.1 Process Description

The facility mixes chemicals in batches to produce insecticides and fungicides.

### 2.2 Control Device Descriptions

**Table 2.1 Insecticides & Fungicides Description**

| Emissions Units / Processes | Control Devices              | Emission Points                    |
|-----------------------------|------------------------------|------------------------------------|
| Insecticides & Fungicides   | (4) Mac Flo Filtration Units | (4) Mac Flo Filtration Unit Stacks |

## Emission Limits

### 2.3 Emission Limits

The emissions from the four separate Mac Flo Filtration Unit stacks shall not exceed any corresponding emissions rate limits listed in Table 2.2.

**Table 2.2 Mac Flo Filtration Unit Stacks Emission Limits<sup>(a)</sup>**

| Source Description        | PM <sub>2.5</sub> <sup>(b)</sup> |                     | PM <sub>10</sub> <sup>(b)</sup> |                     |
|---------------------------|----------------------------------|---------------------|---------------------------------|---------------------|
|                           | lb/hr <sup>(c)</sup>             | T/yr <sup>(d)</sup> | lb/hr <sup>(c)</sup>            | T/yr <sup>(d)</sup> |
| Insecticides & Fungicides | 0.07                             | 0.38                | 0.07                            | 0.38                |

- a) In absence of any other credible evidence, compliance is ensured by complying with permit operating, monitoring, and record keeping requirements.
- b) Particulate matter with an aerodynamic diameter less than or equal to a nominal two point five (2.5) and ten (10) micrometers, including condensable particulate as defined in IDAPA 58.01.01.006.
- c) Pounds per hour, as determined by a test method prescribed by IDAPA 58.01.01.157, EPA reference test method, continuous emission monitoring system (CEMS) data, or DEQ-approved alternative.
- d) Tons per any consecutive 12-calendar month period.

### 2.4 Toxic Air Pollutant (TAP) Limits

Each calendar day, TAPs emissions from powdered based insecticides and fungicides shall not exceed the EL (lb/hr) multiplied by 24 (for TAPs listed in both IDAPA 58.01.01.585 and 586) or the acceptable ambient concentration (mg/m<sup>3</sup>) (for TAPs listed in IDAPA 58.01.01.585) or the acceptable ambient concentration for carcinogens (µg/m<sup>3</sup>) (for TAPs listed in IDAPA 58.01.01.586).

### 2.5 Hazardous Air Pollutant (HAP) Limits

Emissions of any single Hazardous Air Pollutant (HAP) from the entire facility shall not equal or exceed 10 tons per any consecutive 12-calendar month period. Emissions of any combination of HAPs from the entire facility shall not equal or exceed 25 tons per any consecutive 12-calendar month period.

### 2.6 Odors

In accordance with 58.01.01.776.01 the permittee shall not allow, suffer, cause, or permit the emission of odorous gases, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

## **2.7 Opacity Limit**

Emissions from the four Mac Flo filtration unit stacks, or any other stack, vent, or functionally equivalent opening associated with the insecticides & fungicides production, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

## **Operating Requirements**

### **2.8 Insecticides & Fungicides Process Production Limits**

Insecticide and Fungicide production formulated from Pentachloronitrobenzene shall not exceed 4 batches per day.

Insecticide and Fungicide production formulated from Thiram shall not exceed 16 batches per day.

## **Monitoring and Recordkeeping Requirements**

### **2.9 Insecticides & Fungicides Process Production Limits Monitoring**

Each calendar day, the permittee shall monitor and record the production of the insecticides and fungicides processed for those insecticides and fungicides formulated with Pentachloronitrobenzene or Thiram for the previous day in batches per day. Insecticides and fungicides batch production shall be determined by summing the daily batch production over the previous day to demonstrate compliance with the Insecticides and Fungicides Process Production Limits permit condition.

### **2.10 Odors**

The permittee shall maintain records of all odor complaints received. The permittee shall take appropriate corrective action as expeditiously as practicable. The records shall include, at a minimum, the date that each complaint was received and a description of the following: the complaint, any corrective action taken, and the date the corrective action was taken.

### **2.11 Opacity Inspection Records**

The permittee shall conduct a monthly facility wide inspection of potential sources of fugitive emissions during daylight hours and under normal operating conditions to ensure that the methods used to reasonably control fugitive emissions are effective. If fugitive emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive emissions, and the date the corrective action was taken.

### 3 Herbicides

#### 3.1 Process Description

The facility mixes chemicals in batches to produce herbicides.

#### 3.2 Control Device Descriptions

**Table 3.1 Herbicides Description**

| Emissions Units / Processes | Control Devices         | Emission Points               |
|-----------------------------|-------------------------|-------------------------------|
| Herbicides                  | Mac Flo Filtration Unit | Mac Flo Filtration Unit Stack |

### Emission Limits

#### 3.3 Emission Limits

The emissions from the Mac Flo Filtration Unit stack shall not exceed any corresponding emissions rate limits listed in Table 3.2.

**Table 3.2 Mac Flo Filtration Unit Stack Emission Limits<sup>(a)</sup>**

| Source Description | PM <sub>2.5</sub> <sup>(b)</sup> |                     | PM <sub>10</sub> <sup>(b)</sup> |                     |
|--------------------|----------------------------------|---------------------|---------------------------------|---------------------|
|                    | lb/hr <sup>(c)</sup>             | T/yr <sup>(d)</sup> | lb/hr <sup>(c)</sup>            | T/yr <sup>(d)</sup> |
| Herbicides         | 0.07                             | 0.13                | 0.07                            | 0.15                |

- a) In absence of any other credible evidence, compliance is ensured by complying with permit operating, monitoring, and record keeping requirements.
- b) Particulate matter with an aerodynamic diameter less than or equal to a nominal two point five (2.5) and ten (10) micrometers, including condensable particulate as defined in IDAPA 58.01.01.006.
- c) Pounds per hour, as determined by a test method prescribed by IDAPA 58.01.01.157, EPA reference test method, continuous emission monitoring system (CEMS) data, or DEQ-approved alternative.
- d) Tons per any consecutive 12-calendar month period.

#### 3.4 Toxic Air Pollutant (TAP) Limits

Each calendar day, TAPs emissions from powdered based herbicides shall not exceed the EL (lb/hr) multiplied by 24 (for TAPs listed in both IDAPA 58.01.01.585 and 586) or the acceptable ambient concentration (mg/m<sup>3</sup>) (for TAPs listed in IDAPA 58.01.01.585) or the acceptable ambient concentration for carcinogens (µg/m<sup>3</sup>) (for TAPs listed in IDAPA 58.01.01.586).

#### 3.5 Hazardous Air Pollutant (HAP) Limits

Emissions of any single Hazardous Air Pollutant (HAP) from the entire facility shall not equal or exceed 10 tons per any consecutive 12-calendar month period. Emissions of any combination of HAPs from the entire facility shall not equal or exceed 25 tons per any consecutive 12-calendar month period.

#### 3.6 Odors

In accordance with 58.01.01.776.01 the permittee shall not allow, suffer, cause, or permit the emission of odorous gases, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

#### 3.7 Opacity Limit

Emissions from the Mac Flo filtration unit stack, or any other stack, vent, or functionally equivalent opening associated with the herbicides production, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

## **Operating Requirements**

### **3.8 Herbicides Process Production Limits**

Herbicides production formulated from Dacthal shall not exceed 50 batches per any consecutive 12-month period.

Herbicides production formulated from Metribuzin shall not exceed 16 batches per day.

## **Monitoring and Recordkeeping Requirements**

### **3.9 Herbicides Process Production Limits Monitoring**

Each calendar month, the permittee shall monitor and record the production of the herbicides process for those herbicides formulated with Dacthal for the previous month in batches per month. Herbicides batch production shall be determined by summing the monthly batch production over the previous consecutive 12-month period to demonstrate compliance with the Herbicides Process Production Limits permit condition.

Each calendar day, the permittee shall monitor and record the production of the herbicides process for those herbicides formulated with Metribuzin for the previous day in batches per day. Herbicides batch production shall be determined by summing the daily batch production over the previous day to demonstrate compliance with the Herbicides Process Production Limits permit condition.

### **3.10 Odors**

The permittee shall maintain records of all odor complaints received. The permittee shall take appropriate corrective action as expeditiously as practicable. The records shall include, at a minimum, the date that each complaint was received and a description of the following: the complaint, any corrective action taken, and the date the corrective action was taken.

### **3.11 Opacity Inspection Records**

The permittee shall conduct a monthly facility wide inspection of potential sources of fugitive emissions during daylight hours and under normal operating conditions to ensure that the methods used to reasonably control fugitive emissions are effective. If fugitive emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive emissions, and the date the corrective action was taken.

## 4 Flour Processing

### 4.1 Process Description

The facility mixes flour into the chemical batches to produce insecticides, fungicides, and herbicides.

### 4.2 Control Device Descriptions

**Table 4.1 Flour Processing Description**

| Emissions Units / Processes | Control Devices           | Emission Points                 |
|-----------------------------|---------------------------|---------------------------------|
| Flour Processing            | Flour Processing Baghouse | Flour Processing Baghouse Stack |

## Emission Limits

### 4.3 Emission Limits

The emissions from the Flour Processing Baghouse stack shall not exceed any corresponding emissions rate limits listed in Table 4.2.

**Table 4.2 Flour Processing Baghouse Stack Emission Limits<sup>(a)</sup>**

| Source Description | PM <sub>2.5</sub> <sup>(b)</sup> |                     | PM <sub>10</sub> <sup>(b)</sup> |                     |
|--------------------|----------------------------------|---------------------|---------------------------------|---------------------|
|                    | lb/hr <sup>(c)</sup>             | T/yr <sup>(d)</sup> | lb/hr <sup>(c)</sup>            | T/yr <sup>(d)</sup> |
| Flour Processing   | 0.004                            | 0.017               | 0.12                            | 0.542               |

- In absence of any other credible evidence, compliance is ensured by complying with permit operating, monitoring, and record keeping requirements.
- Particulate matter with an aerodynamic diameter less than or equal to a nominal two point five (2.5) and ten (10) micrometers, including condensable particulate as defined in IDAPA 58.01.01.006.
- Pounds per hour, as determined by a test method prescribed by IDAPA 58.01.01.157, EPA reference test method, continuous emission monitoring system (CEMS) data, or DEQ-approved alternative.
- Tons per any consecutive 12-calendar month period.

### 4.4 Opacity Limit

Emissions from the flour processing baghouse stack, or any other stack, vent, or functionally equivalent opening associated with the flour processing baghouse, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

## Operating Requirements

### 4.5 Flour Processing Limits

Flour usage shall not exceed 1,500 tons per any consecutive 12-month period.

### 4.6 Flour Processing Baghouse Pressure Drop

The pressure drop across the baghouse shall be maintained within manufacturer and Operation and Maintenance (O&M) manual specifications. Documentation of the operating pressure drop specifications shall remain on site at all times and shall be made available to DEQ representatives upon request.

## **Monitoring and Recordkeeping Requirements**

### **4.7 Flour Processing Limits Monitoring**

Each calendar month, the permittee shall monitor and record the flour usage for the previous month in tons per month. Flour usage shall be determined by summing the monthly flour usage over the previous consecutive 12-month period to demonstrate compliance with the Flour Processing Limits permit condition.

### **4.8 Flour Processing Baghouse Pressure Drop Recording**

The permittee shall install, calibrate, and operate in accordance with manufacturer specifications, pressure drop monitoring equipment to continuously measure the pressure differential across the baghouse. The permittee shall record the pressure drop across the baghouse once on a weekly basis. A compilation of the most recent two years of records shall be kept on site and shall be made available to DEQ representatives upon request.

### **4.9 Operations and Maintenance Manual Requirements**

The permittee shall maintain an O&M Manual for the baghouse describing the procedures that will be followed to comply with General Provision 5.2. The manual shall contain, at a minimum, manufacturer operating parameters, methods used to measure the pressure drop, and a maintenance schedule. This manual shall remain on site at all times and shall be made available to DEQ representatives upon request. Any changes to the O&M Manual shall be submitted to DEQ for review and comment within 15 days of the change and shall contain a certification by a responsible official.

### **4.10 Opacity Inspection Records**

The permittee shall conduct a monthly facility wide inspection of potential sources of fugitive emissions during daylight hours and under normal operating conditions to ensure that the methods used to reasonably control fugitive emissions are effective. If fugitive emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive emissions, and the date the corrective action was taken.

## 5 General Provisions

### General Compliance

- 5.1 The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the “Rules for the Control of Air Pollution in Idaho.” The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit, the “Rules for the Control of Air Pollution in Idaho,” and the Environmental Protection and Health Act (Idaho Code §39-101, et seq).
- [Idaho Code §39-101, et seq.]**
- 5.2 The permittee shall at all times (except as provided in the “Rules for the Control of Air Pollution in Idaho”) maintain in good working order and operate as efficiently as practicable all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.
- [IDAPA 58.01.01.211, 5/1/94]**
- 5.3 Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules, and regulations.
- [IDAPA 58.01.01.212.01, 5/1/94]**

### Inspection and Entry

- 5.4 Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:
- Enter upon the permittee’s premises where an emissions source is located, emissions-related activity is conducted, or where records are kept under conditions of this permit;
  - Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
  - Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
  - As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

**[Idaho Code §39-108]**

### Construction and Operation Notification

- 5.5 This permit shall expire if construction has not begun within two years of its issue date, or if construction is suspended for one year.
- [IDAPA 58.01.01.211.02, 5/1/94]**
- 5.6 The permittee shall furnish DEQ written notifications as follows:
- A notification of the date of initiation of construction, within five working days after occurrence; except in the case where pre-permit construction approval has been granted then notification shall be made within five working days after occurrence or within five working days after permit issuance whichever is later;
  - A notification of the date of any suspension of construction, if such suspension lasts for one year or more; and

- A notification of the initial date of achieving the maximum production rate, within five working days after occurrence - production rate and date.

[IDAPA 58.01.01.211.01, 5/1/94]

- A notification of the anticipated date of initial start-up of the stationary source or facility not more than sixty days or less than thirty days prior to such date; and
- A notification of the actual date of initial start-up of the stationary source or facility within fifteen days after such date.

[IDAPA 58.01.01.211.03, 5/1/94]

## Performance Testing

**5.7** If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ may, at its option, have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.

**5.8** All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.

**5.9** Within 60 days following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00 and 4/11/15]

## Monitoring and Recordkeeping

**5.10** The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Monitoring records shall include, but not be limited to, the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

## **Excess Emissions**

- 5.11** The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130–136 for excess emissions due to start-up, shut-down, scheduled maintenance, safety measures, upsets, and breakdowns.

[IDAPA 58.01.01.130–136, 4/5/00]

## **Certification**

- 5.12** All documents submitted to DEQ—including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification—shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

## **False Statements**

- 5.13** No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.125, 3/23/98]

## **Tampering**

- 5.14** No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.126, 3/23/98]

## **Transferability**

- 5.15** This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.

[IDAPA 58.01.01.209.06, 4/11/06]

## **Severability**

- 5.16** The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

[IDAPA 58.01.01.211, 5/1/94]